

66-2UL HRV/PORV


Hydraulic / Pneumatic Relay

Diaphragm actuated, spring-loaded relay valve, applicable for service on deluge and pre-action valve trims. The relay will vent or pressurize the hydraulic valve's control chamber, in response to hydraulic or pneumatic pressure.

CERTIFICATION & COMPLIANCE



- UL Listed when installed on OCV Fluid Solutions models



*General representation

FEATURES & BENEFITS


- Available in Brass (Standard) & Stainless Steel 316
- Pressure rating: PN25 / 375psi
- Can be used with any size hydraulic control valve
- Easy to adjust
- Simple design and maximum dependability
- Broad setting range

TECHNICAL DATA

GENERAL		
Pressure Rating	25 bar / 375psi	
Operating Pressure	0.4 -17 bar / 6-250psi	
Fluid Temperature	80°C max / 175°F max	
Weight	1.9 kg / 4.2 lbs	
MATERIALS	STANDARD	OPTIONAL*
Body & Bonnet	Brass	Stainless Steel
Internal Parts	Stainless Steel, Brass	Stainless Steel
Spring	Stainless Steel	Stainless Steel
Elastomers	EPDM	NBR
DIMENSIONS		
H (Height) max	230 mm / 9"	
W (Width)	84 mm / 3.3"	
PORT	SIZE	CONNECTION
1	1/4" NPT	Pressure Command
2	1/2" NPT	Control Chamber
3	1/2" NPT	Vent
4	1/2" NPT	Plugged
5	1/8" NPT	Plugged

*Other materials available upon request. Minimum quantities may apply.

SPRING	COLOR	bar	psi
42 (Standard)	Yellow	0.4-5.5	5-80
47	Green	0.6-9	10-130
50	Red	0.7-17	10-250



OCV companies worldwide reserve the right to make changes without notice including product specification and configuration, content, description(s), dimensions etc. The information herein is subject to change without notice. OCV shall not be held liable for any errors. All rights reserved. © Copyright by OCV.

7400 East 42nd Place • Tulsa, Oklahoma 74145 • USA
 Phone: 1-918-627-1942 • Toll Free: 1-888-OCV-VALV (628-8258) • Email: sales@controlvalves.com