TECHNICAL DATA MODEL 68-710 PILOT



68-710

Pressure Sustaining / Relief 2-Way Pilot Valve

A 2-Way, diaphragm actuated, spring-loaded, pressure sustaining/relief pilot valve, applicable for service on pressure sustaining/relief valve trims. It modulates to maintain a steady, pre-set pressure, upstream of the valve's location. As upstream pressure rises above the set value, the 68-710 opens to allow water flow between its 4 and 3 ports, relieving the water from the valve's control chamber and causing the valve to open. As upstream pressure falls below the set value, the 68-710 throttles, restricting the flow out of the valve's control chamber, limiting the valve's opening or causing it to close (if necessary).



CERTIFICATION & COMPLIANCE

• UL Listed when installed on OCV Fluid Solutions models

FEATURES & BENEFITS


- Wide regulation range (can be set up to 33 bar/480psi)
- Large water passages allow high flow capacity and fast reaction
- Accurate and easy to adjust
- Simple design and maximal dependability


TECHNICAL DATA

| GENERAL | | | | |
|---------------------------|-------------------------|-----------------|--|--|
| Pressure Rating | 40 bar / 580psi | | | |
| Pressure Adjustment Range | 0.5 -33 bar / 7-480psi | | | |
| Fluid Temperature | 80°C max / 175°F max | | | |
| Weight | 1.9 kg / 4.2 lbs | | | |
| MATERIALS | STANDARD OPTIONAL* | | | |
| Body & Bonnet | Brass | Stainless Steel | | |
| Internal Parts | Stainless Steel & Brass | Stainless Steel | | |
| Spring | Stainless Steel | Stainless Steel | | |
| Elastomers | EPDM | NBR | | |
| DIMENSIONS | | | | |
| H (Height) max | 230 mm / 9" | | | |
| W (Width) | 84 mm / 3.3" | | | |
| PORT | SIZE | CONNECTION | | |
| 1 | 1/4" NPT | Upstream | | |
| 2 | 1/2" NPT | Plugged | | |
| 3 | 1/2" NPT | Control | | |
| 4 | 1/2" NPT | Vent | | |

| *Other materials available upon request. Mini | imum quantities may apply. |
|---|----------------------------|
|---|----------------------------|

| SPRING | COLOR | bar | psi |
|---------------|--------|--------|--------|
| 47 (Standard) | Green | 0.7-20 | 10-300 |
| 42 | Yellow | 0.5-10 | 7-150 |
| 50 | Red | 1-33 | 15-480 |





OCV companies worldwide reserve the right to make changes without notice including product specification and configuration, content, description(s), dimensions etc. The information herein is subject to change without notice.

OCV shall not be held liable for any errors. All rights reserved. © Copyright by OCV.

7400 East 42nd Place • Tulsa, Oklahoma 74145 • USA Phone: 1-918-627-1942 • Toll Free: 1-888-OCV-VALV (628-8258) • Email: sales@controlvalves.com